


# TENUS 197

TRF 30 40 90 CL 197 ST WW




## Artech Tenus Round Recessed Trim Downlight

Artech Tenus recessed architectural fixed LED downlight with ingress protection IP44. Total luminous flux up to 3040 lm with overall luminaire efficacy of 125 lm/W. Supplied with fixed output, DALI digital or phase-cut dimmable driver, optional 3 -hour Basic or EMPRO emergency kit. Forged aluminum heat sink with die-cast white or black bezel



<b>Mounting</b>	Recessed (With Trim)
<b>Lamp Type</b>	LED
<b>Wattage</b>	24.3 W
<b>Lumen Output</b>	3040 lm
<b>Efficacy</b>	125 lm/W
<b>Colour Temperature</b>	4000 K
<b>CRI</b>	90+
<b>Beam Angle/ Optic</b>	90°/ Clear
<b>IP Rating</b>	IP44
<b>Control Gear</b>	Fixed Output
<b>Dimensions</b>	197 Dia x 141 mm
<b>Colour Finish</b>	White/ White
<b>MacAdam</b>	3
<b>Service Lifetime</b>	L80/B10-55,000 Hrs



powered by

**TRIDONIC**

Driver details available upon request



Artech lighting strives to ensure all solutions are supplied with the latest technology, we therefore reserve the right to make technical and design changes without prior notice. Electrical connected load and luminous flux are subject to initial tolerance of up +/- 10%. Colour Temperature is subject to a tolerance of +/-150 Kelvin

St Johns Rd, Meadowfield Ind. Estate, Durham, Co. Durham, DH7 8RJ – United Kingdom T: +44(0) 191 3787960 E: [info@artechlighting.com](mailto:info@artechlighting.com) W: [www.artechlighting.com](http://www.artechlighting.com)

